



POWDER-FREE EXAMINATION GLOVES

ORANGE
NITRILE
NON-STERILE
AMBIDEXTROUS
TEXTURED FINGERS
EXTENDED BEADED CUFF
FOR SINGLE USE ONLY
NON LATEX

Our Blaze® high visibility orange glove is perfect for safety and EMS applications. The 10.6" cuff provides enhanced durability with exam grade protection. Textured fingers for increased gripping power.

- High-visibility orange color for safety applications
- Extended, 10.6" cuff for added protection of wrist and forearm
- Meets or exceeds the emergency medical glove requirements of NFPA 1999, Standard on Protective Clothing for Emergency Medical operations, 2013 edition



MEETS OR EXCEEDS



HIGH VISIBILITY ORANGE FOR PROTECTION YOU CAN SEE

PRODUCT CODE	PACKAGING
S N481	100 Gloves/Box
M N482	10 Boxes/Case
L N483	
XL N484	
XXL N485	

GLOVE PROFILE	ASTM D 6319	BLAZE®
Length <i>mm (inches)</i>	min. 220 (8.7)	min. 270 (10.6)
Cuff Thickness <i>mm (mils)</i>	n/a	0.10 (3.9)
Palm Thickness <i>mm (mils)</i>	min. 0.05 (2.0)	0.13 (5.1)
Finger Thickness <i>mm (mils)</i>	min. 0.05 (2.0)	0.20 (7.9)
Tensile Strength <i>Before Aging</i>	min. 14	33
<i>After Aging</i>	min. 14	37
Elasticity/Elongation <i>Before Aging</i>	min. 500	500
<i>After Aging</i>	min. 400	500
Pinhole Defect Rate* <i>(AQL)</i>	max. 2.5	1.5

* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED
INDUSTRIES